



KALE ENTERPRISES, INC.

370 East Plaza Drive
 Mooresville, NC 28115

O: 704.658.0444
 F: 704.658.1965

CONTRACTOR SOD STAPLES

STANDARD REQUIREMENTS:

CONTRACTOR SOD STAPLES ARE USEFUL FOR SECURING AND STABILIZING EROSION BLANKETS AND GEOTEXTILE FABRIC. THEY ARE SUPPLIED WITH A 6"x1"x6" OR 12"x1"x12" CONFIGURATION WITH AN ANGLED CUT CREATING A POINT FOR EASY INSERTION INTO THE SOIL.

CHEMICAL REQUIREMENTS:

CONTRACTOR SOD STAPLES ARE PRODUCED USING A C1006 TO C1018 GRADE OF CARBON STEEL AS SPECIFIED IN ASTM A510 AND ASTM A1040. THE WIRE USED TO PRODUCE THE SOD STAPLES WILL COMPLY WITH ASTM A853.

PHYSICAL REQUIREMENTS:

CONTRACTOR SOD STAPLES ARE PRODUCED FROM AN 11-GAUGE WIRE. THE SIZE TOLERANCE FOR THE WIRE IS .112" TO .115". THE DISTANCE ACROSS THE TOP OF THE BRIDGE OF THE STAPLE WILL RANGE FROM 1.113" TO 1.25". THE LEG LENGTHS WILL BE 6" OR 12" +0.00"/-0.250"

PACKAGING:

CONTRACTOR SOD STAPLES ARE SUPPLIED IN 1,000CT (6") AND 500CT (12") BOXES. THE STAPLE WEIGHT OR NET BOX WEIGHT WILL BE APPROX. 36 POUNDS. BOXES ARE PACKAGED ON A PALLET RANGING FROM 54-60 BOXES PER SKID.